

# GALLERY



# M-Touch

Martin M-Touch uses M-PC as software that will run on a Windows PC and can be downloaded  $\underline{here}$ .

Martin M-Touch is a powerful yet simple control surface for the Martin M-Series controllers, the most affordable professional lighting solutions on the market. Fully compatible with all M-Series consoles and M-PC software, Martin M-Touch is a plug-and-play solution with an innovative control surface like no other lighting console. 14 touch faders allow control of playbacks and fixture parameters while 20 velocity-controlled pads allow for new types of effects. Additional programming buttons such as Record, Edit, Update, Load and Clear are accessible directly from the M-Touch control panel. Martin M-Touch comes with one DMX 512 Universe for direct control of any compatible DMX device.

Truly affordable console surface for both smaller applications and professional use

# Rugged aluminum design for durability

The most powerful controller of its class with a full 512 DMX channels, expandable to 65,000 channels

### FEATURES

- Truly affordable console surface for both smaller applications and professional use
- · Rugged aluminum design for durability
- The most powerful controller of its class with a full 512 DMX channels, expandable to 65,000 channels

### TECHNICAL SPECIFICATIONS

Physical Length: 394 mm (15.5 in.) Width: 218.5 mm (8.6 in.) Height: 46.5 mm (1.8 in.) Weight: 1.5 kg (3.3 lbs.)

Control/User Interface Bank Navigation Up/Down with numerical display Main Go section: Snap, Release, Pause and Go buttons Command Buttons: Record, Edit, Update, Load, Clear Multifunction Mode Select button Fixture Selection buttons: Last, Next, Highlight 4 x Parameter Select buttons 4 x Parameter Adjust touch faders 10 x Function velocity pads Playback 10 x Playback touch faders with 3 buttons (2 x touch pad, 1 x velocity pad) System integration Unlocks 1 x DMX universe when connected to M-PC™ Construction Housing: Aluminum, steel, plastic Mounting: VESA 75x75, 100x100 Security: K-Lock locking slot IP Rating: IP20

Connections DMX data link: 1 x 5-pin locking XLR Windows PC: USB 2.0 Electrical Power source: 5 VDC over USB Maximum current: 500 mA



©2015 Martin Professional Olof Palmes Allé 18 • 8200 Aarhus N • Denmark • Phone: +45 87 40 00 00 • Fax: +45 87 40 00 10 • www.martin.com Images contained in this brochure have been converted to CMYK and are not necessarily representative of actual colors. Specifications are subject to change without notice Thermal Operating temperature: 0° – 50° C (32° – 122° F) I ncluded I tems USB cable 1.5m (4.9 ft.)

Accessories Martin™ M-Sync SMPTE USB: P/N 90703020 M-PC 2U / M-DMX: P/N 90737070 Martin One-Key with M-PC Pro-64 /LJ-4 License: P/N 70758460 Rackmount bracket: P/N 91611690

Related Ltems M-Series Submaster Module: P/N 90732170 M-Series Playback II Module: P/N 90732190 Martin™ M-Play: P/N 90737030 Martin™ M-PC Pro 64 / LightJockey 4 Controller Kit: P/N 90737060 Ordering Information Martin M-Touch: P/N 90737040



