



PL 8X

Description

Specifications

Ceiling speaker

The PL8X is a ceiling speakers featuring elegant and innovative design that can be flush-mounted in false ceilings or panels. Incorporating a 200 mm (8") loudspeaker.

Both have a coaxial 25 mm (1") tweeter placed on a bridge support. The speakers are equipped with a line transformer that enables direct connection to constant voltage systems at 70 V or 100 V. The multiple sockets on the transformer make it possible to select the output power from among several values.

Installation is quick and easy thanks to a special three-hook system that avoids the need for using screws and pallet or other attachment elements.

- Main body in plastic material, steel grille color white RAL 9003.
- Protection IP 44.

SPECIFICATIONS

Type	Ceiling speaker with transf.
Installation system	Flush mount
Nominal/maximum power	20/40 W
Constant voltage	100-70 V
Impedance	8 Ω
Frequency response	60 Hz-20 kHz
Sensitivity	93 dB (1W/1m)
Maximum sound pressure	109 dB 1 m
Angle of coverage	(-6dB): 80°
Dimensions	Ø 247x88 mm.
Maximum protrusion	8 mm.
Flush-mounting hole	Ø 224 mm.
Weight	1,8 Kg.
Accessories included	-
Optional accessories	-
Speaker	8" woofer with coaxial tweeter
Protection level	IP 44
Connectors	-